


Section 10	DESIG	ney	DRAWN BY	DART AEROSPACE L VICTORIA INTERNATIONAL AIRPORT, CA	
	CHECK	MAY	APPROVED	DEO 9088	REV. A SHEET 1 OF 1
	DATE			TITLE	SCALE
	97.1	97.10.15		204 SKIDTUBE STEP CHANGE	NTS
	Α		97.10.15	NEW ISSUE	

DART ENGINEERING ORDER

TO AMEND DART DRAWINGS D2590 REV B



- 1. CUT TUBE TO DIMENSIONS SHOWN AND DE-BURR
- 2. REMOVE RIDGE ON OUTSIDE OF TUBE
- 3. LOCATE D2706 STEP
- 4. TRANSFER DRILL Ø0.191 TO SKIDTUBE (3 PLACES) AND REMOVE SWARF
- 5. INSTALL MS20600AD6W4 (OR CR9163-6-4) RIVETS ON SIDES (2 PLACES)
- 6. INSTALL MS20600AD6W8 (OR CR9163-6-8) RIVETS ON TOP (1 PLACE)
- 7. SEAL EDGE OF D2706 STEP WITH SIKAFLEX-241 (OR EQUIVALENT) SEALANT PER MANUFACTURER'S SPECIFICATION